

Main technical characteristics of drying kilns

MODEL	DIMENSIONS (WIDTH X DEPTH X HEIGHT) m	AVERAGE LOADING CAPACITY m ³	AXIAL FANS No.	FANS Ø	POWER OF EACH FAN Kw	FAN DELIVERY m ³ /h	MAX. INSTALLED HEATING POWER Kw		STANDARD HEATING POWER Kw	DAMPERS No.	DAMPERS Ø mm
							min.	max			
EPL 45.42.41	4,5 x 4,2 x 4,1	20	2	800	3,0	30.000	80	100	50	2 + 2	370
EPL 45.57.41	4,5 x 5,7 x 4,1	30	2 S	800	3,0	34.000	120	180	90	2 + 2	370
EPL 45.72.41	4,5 x 7,2 x 4,1	40	3	800	3,0	30.000	160	240	120	2 + 2	370
EPL 45.87.41	4,5 x 8,7 x 4,1	50	3	800	4,0	38.000	200	300	150	2 + 2	370
EPL 65.42.41	6,5 x 4,2 x 4,1	30	3	800	3,0	30.000	120	180	90	2 + 2	370
EPL 65.57.41	6,5 x 5,7 x 4,1	40-45	3 S	800	3,0	34.000	180	270	135	2 + 2	370
EPL 65.72.41	6,5 x 7,2 x 4,1	55-60	4	800	3,0	30.000	240	360	180	2 + 2	500
EPL 65.87.41	6,5 x 8,7 x 4,1	65-70	4	800	4,0	38.000	280	420	210	2 + 2	500
EPL 85.57.41	8,5 x 5,7 x 4,1	55-60	5	800	3,0	30.000	240	360	180	3 + 3	370
EPL 85.72.41	8,5 x 7,2 x 4,1	70-75	6	800	3,0	30.000	300	450	225	3 + 3	500
EPL 85.87.41	8,5 x 8,7 x 4,1	90-95	6	800	4,0	38.000	380	570	285	3 + 3	500
EPL 85.102.41	8,5 x 10,2 x 4,1	100-110	6 S	800	4,0	43.500	420	630	315	3 + 3	500
EPL 125.57.41	12,5 x 5,7 x 4,1	80-85	7	800	3,0	30.000	340	510	255	4 + 4	370
EPL 125.72.41	12,5 x 7,2 x 4,1	100-110	8	800	3,0	30.000	440	660	330	4 + 4	500
EPL 125.87.41	12,5 x 8,7 x 4,1	130-140	8	800	4,0	38.000	560	840	420	4 + 4	500
EPL 125.102.41	12,5 x 10,2 x 4,1	150-160	8 S	800	4,0	43.500	640	960	480	4 + 4	500
EPL 132.72.41	13,2 x 7,2 x 4,1	105-115	9	800	3,0	30.000	460	690	345	4 + 4	500
EPL 132.87.41	13,2 x 8,7 x 4,1	135-145	9	800	4,0	38.000	580	870	435	4 + 4	500
EPL 132.102.41	13,2 x 10,2 x 4,1	155-165	9 S	800	4,0	43.500	660	990	495	4 + 4	500